

RANGER™ 4x4



RANGER XP™



RANGER HD™



Engine	RANGER™ 4x4	RANGER XP™	RANGER HD™
Displacement/HP	499cc/32 hp	683cc/40 hp	683cc/40 hp
Cooling	Liquid-cooled	Liquid-cooled	Liquid-cooled
Engine Type	4-valve, 4-stroke single cyl.	4-valve, 4-stroke twin cyl.	4-valve, 4-stroke twin cyl.
Top Speed	41 mph	50 mph	50 mph
Lubrication	Dry sump	Wet sump	Wet sump
Oil Capacity	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.
Carburetion	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Fuel Capacity	9.0 gal./34 ltr.	9.0 gal./34 ltr.	9.0 gal./34 ltr.
Coolant Capacity	2.3 qts./2 ltr.	3.25 qts./3 ltr.	3.25 qts./3 ltr.
Alternator	250 watts	500 watts	500 watts
Starting/Battery	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH
Drivetrain			
Transmission	Automatic	Automatic	Automatic
Gear Range	In-line	In-line	In-line
Drive	4-wheel shaft drive	4-wheel shaft drive	4-wheel shaft drive
Suspension			
Front Details	Adjustable Dual A-Arms	Adjustable Dual A-Arms	Adjustable Dual A-Arms
Rear Details	Independent Rear Suspension	Independent Rear Suspension	Self-Leveling Suspension™ with Nivomat® Shocks
Front Suspension	9.63 in. Dual A-Arm/24.5 cm	9.63 in. Dual A-Arm/24.5 cm	9.63 in. Dual A-Arm/24.5 cm
Rear Suspension	9.0 in. Dual A-Arm/22.9 cm	9.0 in. Dual A-Arm/22.9 cm	7.5 in. Dual A-Arm/19 cm with load-leveling shocks
Center Suspension	N/A	N/A	N/A
Tires (front/rear)	25 x 10-12/25 x 11-12	25 x 10-12/25 x 11-12	26 x 9-12/26 x 11-12
Dimensions			
Wheelbase	76 in./193 cm	76 in./193 cm	76 in./193 cm
Turning Radius	158 in./401 cm	158 in./401 cm	166 in./422 cm with Power Steering
Dry Weight	1,214 lbs./550 kg	1,237 lbs./561 kg	1,262 lbs./572 kg
Ground Clearance	12 in./30 cm	12 in./30 cm	12 in./30 cm
Length/Width/Height	113 in./60 in./75 in. (287 cm/152 cm/190 cm)	113 in./60 in./75 in. (287 cm/152 cm/190 cm)	113 in./60 in./75 in. (287 cm/152 cm/190 cm)
Brakes	4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic disk
Parking Brake	Hand-activated	Hand-activated	Hand-activated
Load Capacity			
Box Dimension/Capacity	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/ 1,000 lbs. (454 kg)	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/ 1,000 lbs. (454 kg)	54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/ 1,000 lbs. (454 kg)
Payload Capacity	1,500 lbs./681 kg	1,500 lbs./681 kg	1,500 lbs./681 kg
Hitch Tow Capacity	1,500 lbs./681 kg	2,000 lbs./907 kg	2,000 lbs./907 kg
Cargo System	Lock & Ride®	Lock & Ride	Lock & Ride
Seating	3	3	3
Skid Plate	Full	Full	Full

RANGER CREW™**RANGER 6x6****RANGER RZR™****RANGER RZR S**

683cc/40 hp	683cc/40 hp	760cc	760cc H.O.
Liquid-cooled	Liquid-cooled	Liquid-cooled	Liquid-cooled
4-valve, 4-stroke twin cyl.	4-valve, 4-stroke twin cyl.	Twin cyl.	Twin cyl.
44 mph	44 mph	55 mph	63 mph
Wet sump	Wet sump	Wet sump	Wet sump
2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.	2 qts./1.9 ltr.
Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
9.0 gal./34 ltr.	9.0 gal./34 ltr.	7.25 gal./27.4 ltr.	7.25 gal./27.4 ltr.
3.3 qts./3 ltr.	3.3 qts./3 ltr.	4.8 qts./4.5 ltr.	4.8 qts./4.5 ltr.
500 watts	500 watts	500 watts	500 watts
Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH	Electric/12V-30 AH
Automatic	Automatic	Automatic PVT	Automatic PVT
In-line	In-line	In-line P/R/N/L/H	In-line P/R/N/L/H
4-wheel shaft drive	6-wheel shaft drive	4-wheel shaft drive	4-wheel shaft drive
MacPherson Strut	MacPherson Strut	Double A-Arm with antisway bar	Double A-Arm
Independent Rear Suspension	Swingarm Dual Shocks	Rolled independent with antisway bar	Rolled independent with antisway bar
8.0 in./20.32 cm	8.0 in./20.32 cm	9.0 in./22.9 cm	12 in. Fox Podium® (comp adjust/res.)/30 cm
9.0 in./22.9 cm	6.25 in./15.9 cm	9.5 in./24 cm	12 in. Fox Podium® (comp adjust/res.)/30 cm
N/A	Prog. rate, fully ind. A-Arm, 5.3 in./13.3 cm of travel	N/A	N/A
26 x 9-12/26 x 11-12	25 x 10-12/25 x 11-12	25 x 8-12/25 x 10-12	26 x 9-12/26 x 12-12
108 in./274 cm	90 in./229 cm	77 in./196 cm	77 in./196 cm
224 in./567 cm	186 in./472 cm	101.5 in./258 cm	149.5 in./380 cm
1,460 lbs./662 kg	1,410 lbs./640 kg	945 lbs./429 kg	1,000 lbs./454 kg
11 in./28 cm	7.2 in./18 cm	10 in./25 cm	12.5 in./32 cm
145 in./60 in./75 in. (368 cm/152 cm/190 cm)	120 in./60 in./75 in. (305 cm/152 cm/190 cm)	102 in./50 in./69 in. (259 cm/127 cm/75 cm)	106 in./60.5 in./70.5 in. (269 cm/154 cm/179 cm)
4-wheel hydraulic disk	4-wheel hydraulic disk	4-wheel hydraulic	4-wheel hydraulic
Hand-activated	Hand-activated	N/A	N/A
54 in. x 36.5 in. x 11.5 in. (143 cm x 93 cm x 31.5 cm)/1,000 lbs. (454 kg)	54 in. x 42.5 in. x 11.5 in. (143 cm x 108 cm x 31.5 cm)/1,250 lbs. (567 kg)	42 in. x 22 in. (107 cm x 56 cm)/300 lbs. (136 kg)	42 in. x 22 in. (107 cm x 56 cm)/300 lbs. (136 kg)
1,750 lbs./794 kg	1,750 lbs./794 kg	740 lbs./336 kg	740 lbs./336 kg
2,000 lbs./907 kg	2,000 lbs./907 kg	1,500 lbs./681 kg	1,500 lbs./681 kg
Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
6	3	2	2
Full	Full	Full	Full